

Product data sheet


URBINO LED 55W 6450LM 4000K IP66 O60 - FOR TOWN ROADS GRAY I
130222.5L041.361

LUG



Professional streetlight luminaire for LED light sources. High efficacy to 156 lm/W Mounting: on pillar $\varnothing 60/48$ mm, on pillar $\varnothing 76$ mm - modification .829, on outriggers $\varnothing 60/48$ mm, on outriggers $\varnothing 76$ mm - modification .829. Body: high pressure die-cast aluminum. Lateral Surface Wind Exposed: 0.039 m². Power supply efficiency >95% Power: 220-240V 50/60Hz. Lifetime LED (L90): 100 000 h Available on request: DALI, DIM 1..10V, LLOC, twilight sensor, knife switch, 10kV surge protection, NTC. Additional information: Tilt adjustment: -15° to +15° (every 5°). Additional equipment: additional anti-corrosive protection (index extension: .985), access to the driver chamber without the use of tools (index extension: .825), luminaire with holder for mounting on a $\varnothing 76$ mm pillar (index extension: .829). Other remarks: the pole and boom are not part of the luminaire. Warranty: 5 years. Application: express roads, local roads, town roads, residential area roads, pedestrian crossings, area lighting, avenues, promenades, cycle paths. Type of optics: O60 - for town roads

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	55 W	CRI	70
Total flux	6450 lm	LOR	100%
Luminous efficacy	117 lm/W	Total power	55 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 21.65 in

Width: 9.84 in

Height: 3.94 in

Adjustability

Tiltable

Design

Color of housing: Silver gray

Electric

System power: 55 W

Appliance Class: I

Protection

IP: 66

IK: 09