



# Product data sheet

SRT-SYSTEM IP20-SRGLP/1500 LED - GERÄTETRÄGER FIX DIFFUSOR PRISMIERT MIT INNENLIEGENDER LÄNGSPRISMA...  
11000 840 (PHI-EL=925LM) ET NL-3H VW RAL 9016 (SRT+19150007040)  
REGIOLUX



SRT-Quick-fit mounting system, Device mount, Modullänge/1500. Device mount made of a galvanised, profiled steel sheet; surface coated with polyester resin. Tool-free attachment with integrated side lever catches for rapid fitting in the mounting rail. LED unit in housing length for an optically seamless light run. Housing colour traffic white RAL 9016. Diffuser optics, Light distribution direct/indirect narrow/wide distribution by means of Prismatic diffuser with internal longitudinal prisms of PMMA plastic, creates a uniform, homogeneous finish with a brightening effect on the ceiling.. The light source and driver are removable in accordance with the EU 2019/2020 ecodesign requirements and can be replaced in the factory. Electrical connection by means of a fixed, 5-pin, quick-fit plug connector and a free choice of phases. Integrated guide for fast contacting; Luminaire status by visible status LED in luminaire (NL-B3); Luminous flux in emergency light mode 925 lm. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system. Dimensions (LxWxH): 1531mm x 63mm x 54mm Beam angle: 45° (C0)/100 ° (C90) Placement: LED, Colour rendering/Light colour CRI ≥ 80 / 4000K Colour tolerance: 3SDCM Photobiological safety (Luminaire): RG1 LED service life: 50000h L80/B10 (Tq 25°C) Nominal luminous flux: 10921lm Nominal luminous flux-emergency lighting mode: 925lm Luminaire luminous efficiency: 171lm/W Control gear: Electronic driver 3h emergency lighting (1 pcs.) System output: 64W Energy efficiency class/light source: B Mains voltage: 230V Mains frequency: 50Hz Impact resistance (IK rating): IK03 (10°C bis 25°C) Ambient temperatur: ta 10°C to 25°C UGR lat./long.: 25.1 / 25.0 Certification mark: IP20, Protection class I, F, HACCP DIN10500/Food/IFS-application-related suitability (see certificate)/BRC, Indoor, CE Warranty period: 5 years Regiolux GmbH Type: SRGLP /1500 LED 11000 840 ET NL-B3 vw RAL 9016 Article number: 19150007040 Product deep link: <https://www.regiolux.de/en/article/19150007040> General warranty conditions: [www.regiolux.de/en/Service/Warranty](http://www.regiolux.de/en/Service/Warranty)

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          |          | CCT         | 4000 K |
| Nominal lamp power | 64 W     | CRI         | 80     |
| Total flux         | 10921 lm | LOR         | 100%   |
| Luminous efficacy  | 171 lm/W | Total power | 64 W   |

## Mounting mode

Ceiling mounted, Contact rail

## Shape and measurements

Length: 60.43 in

Width: 2.56 in

Height: 3.39 in

## Design

Color of housing: White

## Electric

System power: 64 W

Appliance Class: 0

## Protection

IP: 20

IK: 03

Designation labels: CE