Product data sheet


OUTDOOR LIGHTING
V1-S1-H0702-40L30-6522540 URAGAN URBAN 225W 4000K
VARTON



IP 65 IK 08

High-power modular luminaire for outdoor lighting. Cast aluminum housing. Multifunctional adjustable spigot. Application: outdoor areas. Installation: side-entry mounted (Ø48mm-60mm), surface-mounted (dock not included in package). Color of housing: Grey Power factor: 0,95 AC frequency, Hz: 50 Flicker, %: 5 Climatic modification and category of placement: УХЛ1 Protection class: I Suitable for top end size, mm: 48...60 Mounting method: Side-entry Ingress protection (IP): IP65 Impact resistance: IK08 Color rendering index: 70-79 Nominal voltage, V: 220...230 https://www.varton.ru/products/ulichnoe-osveshchenie/uragan/uragan-urban-dlya-goroda/svetodiodnyy-svetilnik-varton-ulichnyy-uragan-urban-225-vt-4000-k/

Light output 1



1 x LED

Nominal lamp power	225 W	LOR	100%
Lamp flux	30375 lm	Total flux	30375 lm
Luminous efficacy	135 lm/W	Total power	225 W
CCT	4000 K		
CRI	70		

Mounting mode

Pole integrated

Shape and measurements

Length: 31.30 in
Width: 12.40 in
Height: 3.94 in

Adjustability

Fixed

Electric

System power: 225 W

Protection

IP: 65
IK: 08