Product data sheet


NOVIA ROW 1200 12W 1440LM 4000K, L-1205MM, WHITE, DALI, DIRECT
LIUS0049--
SCHRACK TECHNIK



IP 20

Versatile linear luminaire for continuous lighting systems in offices, corridors, and general areas. High efficiency, flexible configuration, and modular expandability allow precise adaptation to various lighting requirements. Switchable color temperature: 3000 K / 4000 K 4 selectable power levels Direct light distribution, extendable to direct/indirect lighting via optional rear-mounted indirect module DALI dimmable, direct and indirect components controlled simultaneously UGR < 19 only at the lowest power level Modular system for continuous light lines (connectors) Mounting options: ceiling, wall, or suspended

Light output 1



1 x LED

Nominal lamp power	12 W	LOR	100%
Lamp flux	1440 lm	Total flux	1443 lm
Luminous efficacy	120 lm/W	Total power	12 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 47.44 in
Width: 2.24 in
Height: 2.99 in

Adjustability

Fixed

Design

Material impression: Aluminum, Plastic
Color of housing: White

Glare protection

Glare protection: UGR < 19

Electric

System power: 12 W
Color adjustable
Appliance Class: I

Protection

IP: 20
Designation labels: CE

Other operating numbers

Ambient temperature range: -4...113°F