


# Product data sheet

CASSIOPEA  
756714  
FLOS



• Recessed luminaire for outdoor installation in the ground where recessing depth are limited (up to 120mm) • Configuration: die-cast aluminium structure. EN AB-47100 alloy (low copper content) in round and square version. • Double layer coating for high resistance to corrosion: The low copper Aluminium alloy is painted with a double coat using powders which are complaint with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents).The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting.

## Light output 1



1 x Metal halide lamp			
Nominal lamp power	35 W	Socket	G8D.5
Lamp flux	3400 lm	LOR	37%
Luminous efficacy	36 lm/W	ULOR	37%
CCT	3000 K	Total flux	1270 lm
CRI	81	Total power	35 W

## Mounting mode

Floor recessed

## Shape and measurements

Height: 4.61 in  
Diameter: 12.20 in

## Adjustability

Fixed

## Electric

System power: 35 W  
Appliance Class: I

## Protection

IP: 67  
IK: 09