


Product data sheet

SWEEP 700 DELTA WHITE CLO TW - 4-65K E-ST MASTER
54961-477
FAGERHULT



Installation Two point suspension c/c 48 mm. Connection For permanent connection with 230 V; built-in LED driver. Snap-in terminal block 5x2.5 mm². 1-phase through-wiring possible. Surface mounted mains cable possible 180°. Design Luminaire body in plastic lacquered in various colours. Supplied with 3 m wire, 2,2 m transparent cable and white, plastic ceiling cup. Height adjustment is done on the luminaire using a friction lock. The ceiling cup handles inclined ceilings up to 20°. Louvre Opal - opal acrylic diffuser. Delta – microprism louvre in acrylic (PMMA). Light distribution Delta/Opal Ø 500 – Direct/indirect 55/45. Delta Ø 700 – Direct/indirect 60/40. Opal Ø 700 – Direkt/indirekt 65/35. Dimming DALI/phase-pulse control as standard. Tunable White and e-Sense Tune on request.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	73 W	CRI	80
Total flux	6693 lm	LOR	100%
Luminous efficacy	92 lm/W	ULOR	55%
		Total power	73 W

Mounting mode

Pendant

Electric

System power: 73 W

Shape and measurements

Length: 27.56 in
Width: 27.56 in
Height: 14.09 in

Protection

IP: 20

Adjustability

Fixed