

Product data sheet

VEKTOR BAS XL 3K SENSOR


E7214582

CARDI



Vektor Bas är en allmänljusarmatur IP44 i slimmad design för trapphus, garage, korridorer och allmänna utrymmen. Armaturen har en diffuserad linjeprismatisk kupa som ger en mjuk ljusfördelning. Monteras dikt tak, lina, på vägg eller konsol. Godkänd för omgivningstemperatur -20°C till +60°C. Stomme av vitlackerad stålplåt, gavlar av vit polykarbonat, kupa av frostad linjeprismatisk akryl. Införingshål, knockout Ø 16 mm i vardera gavel samt 2st Ø 19 mm införingshål på ovansidan. Insticksplint i mitten av armaturen 5x2x2,5 mm². Armaturen har inbyggd mikrovågssensor med rörelse- och dagsljusavkänning. Tiden innan armaturen släcker kan ställas mellan 5 sekunder och upp till 30 minuter. Armaturen har en utgång från sensorn som kan tända och släcka upp till 3 st armaturer, dock max 400W. Sensorn klarar att detektera upp till 6m montagehöjd.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	28 W	CRI	80
Total flux	4300 lm	LOR	100%
Luminous efficacy	154 lm/W	ULOR	7%
		Total power	28 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 49.83 in

Width: 6.89 in

Height: 1.80 in

Adjustability

Fixed

Electric

System power: 28 W

Appliance Class: I

Integrated sensors

Integrated sensors: Daylight sensor, Motion sensor

Protection

IP: 44

IK: 06