

Product data sheet

O55-W250 LED 3000 840 MB
GLAMOX




IP
66

IK
09

Light source LED 3000 - 8000 lumen out Colour temperature 3000/4000 K, CRI Ra 80, MacAdams 3 Driver Fixed output (HF) or DALI dimmable (10-100%). Body material & colour Housing in die-cast aluminium. Double layer black (RAL 9005), anthracite (close to RAL 7024) or aluminium grey (RAL 9006) polyester powder coated paint finish. Tempered safety glass cover. Silicone gasket. Screws made of stainless steel. Accessories Bracket and twin bracket for pole Ø60 mm. Connection 2 x M20 cable glands (cable Ø8 - 12 mm). 3/5 pole 2.5 mm² push-in terminal block. Outdoor use requires suitable flexible cables assuring the water tightness of the cable gland. Optics Medium beam (MB) and asymmetric (ASY). Wind exposed surface 0.11 m² Protection against surges Up to 6kV.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	35 W	CRI	80
Total flux	3300 lm	LOR	100%
Luminous efficacy	94 lm/W	ULOR	84%
		Total power	35 W

Mounting mode

Ceiling mounted, Wall mounted

Electric

System power: 35 W

Shape and measurements

Length: 19.49 in
Width: 9.84 in
Height: 2.95 in

Protection

IP: 66
IK: 09

Adjustability

Tiltable

Design

Color of housing: Black, Anthracite / graphite, Silver gray