Product data sheet

LD141DR 6.4W 500MA MB
LD141DR-E3-500-MB
LIGHTGRAPHIX



LD141DR Ø64mm Deep Recessed Uplight. IP67. Constant Current. 6.4W 500mA 19° Medium beam. The LD141DR has been designed for exterior applications that require super low glare, with the lens assembly recessed 51mm into the body. Compact in size, it offers a powerful output with a large range of features. The E3 engine delivers a high output of 440lm and 12° narrow beam and colour temperatures from 2700K to 5000K. Designed with a repairable light engine, the LD141DR offers a circular, low glare, solution for a wide range of exterior rated applications.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	6.4 W	CRI	85
Total flux	442 lm	LOR	100%
Luminous efficacy	69 lm/W	ULOR	100%
		Total power	6.4 W

Mounting mode

Floor recessed

Shape and measurements

Height: 3.62 in
Diameter: 2.52 in

Adjustability

Fixed

Design

Material impression: Matt, Bronze, Glass, Brass, Gloss, Stainless steel
Color of housing: Black, White, Anthracite / graphite, Silver gray

Electric

System power: 6.4 W
Controller: Dimmable 0..10V, Dimmable 1..10V, DMX, DALI
Appliance Class: III

Protection

IP: 67
IK: 08
Designation labels: CE

Other operating numbers

Ambient temperature range: -4...122°F