


Product data sheet


FLEXBAR DIFFUSER - 25 W - OPAL - RECESSED - CONTINUOUS - CORNER - SECONDARY RIGHT HAND
FXD25CSRO
THORLUX LIGHTING



IP
20


Slimline linear luminaires. Elegant linear luminaire ideal for a wide range of applications. The uninterrupted diffuser creates striking lines of light across the ceiling, whether mounted on the surface, suspended, or recessed. The range includes individual, continuous, and corner lengths to allow designers to be flexible with their lighting designs. The dropped diffuser, available in opal and low-glare, provides upward light, creating a softer appearance whilst supporting illumination on the walls and ceiling, and aiding compliance to EN 12464-1 and LG7. Applications: offices, education, meeting rooms, healthcare, circulation, leisure, and retail.

Light output 1



1 x LED			
Nominal lamp power	13 W	LOR	100%
Lamp flux	1839 lm	ULOR	9%
Luminous efficacy	141 lm/W	Total flux	1839 lm
CCT	4000 K	Total power	15 W
CRI	80		

Light output 2



1 x LED			
Nominal lamp power	12 W	LOR	100%
Lamp flux	1796 lm	ULOR	9%
Luminous efficacy	150 lm/W	Total flux	1796 lm
CCT	4000 K	Total power	14 W
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 34.25 in

Width: 2.24 in

Height: 2.68 in

Adjustability

Fixed

Electric

System power: 29 W

Protection

IP: 20