


Product data sheet

REO OK 93033 S2
202 372 811 932
DELTA LIGHT




Luminaire, ceiling recessed (indoor use) from Deltalight, named REO OK 93033 S2, available in the colour(s): black, white. For recessed mounting, a round opening with a diameter of 98 mm is needed and a min. depth for recessing of 65 mm. This luminaire is equipped with LED array 5,8-8,6W / CRI>90 (R9: 52) / 3000K / 787-1089lm with an optional driver, suitable for currents of 350mA to 500mA. Light distributor: reflector 33°.

Light output 1



1 x LED			
Nominal lamp power	6 W	LOR	73%
Lamp flux	787 lm	Total flux	573 lm
Luminous efficacy	131 lm/W	Total power	8 W
CCT	3000 K		
CRI	90		



1 x LED			
Nominal lamp power	9 W	LOR	73%
Lamp flux	1089 lm	Total flux	792 lm
Luminous efficacy	121 lm/W	Total power	12 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.12 in
Diameter: 3.23 in
Weight: 0.3 kg

Electric

System power: 8-12 W
Appliance Class: II

Protection

IP: 20
Designation labels: CE