
Product data sheet


SINUS SUSP. DI/ID WHITE SAT. 2950MM
R33H295-9016E2930L3S
PLANLICHT



IP 40


low output LED 3000K CRI 90 235,9W 27195lm DALI https://katalog.planlicht.com/en-gb/fam-sinus/

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	29.49 W	CRI	90
Total flux	3399 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	29.49 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	29.49 W	CRI	90
Total flux	3399 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	29.49 W

Light output 3 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	29.49 W	CRI	90
Total flux	3399 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	29.49 W

Light output 4 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	29.49 W	CRI	90
Total flux	3399 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	29.49 W

Light output 5 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	29.49 W	CRI	90
Total flux	3399 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	29.49 W

Light output 6 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	29.49 W	CRI	90
Total flux	3399 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	29.49 W

Light output 7 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	29.49 W	CRI	90
Total flux	3399 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	29.49 W

Light output 8 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	29.49 W	CRI	90
Total flux	3399 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	29.49 W

Mounting mode

Pendant

Shape and measurements

Length: 116.14 in
Width: 116.14 in
Height: 3.94 in

Adjustability

Fixed

Electric

System power: 235.9 W

Protection

IP: 40