



Product data sheet

1282 MERIDIANA LED 4000K CRI 80 9W CLD
423095-00
DISANO



Housing: in die-cast aluminium. Optics: in high-performance prismatic and polished aluminium. Diffuser: tempered glass, 4 mm thick, resistant to thermal shock and impact (UNI EN 12150-1:2001). Coating: pre-treatment of metal surface, polyester powder coating to ensure resistance to corrosion and salt spray fogs, UV stabilised. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. With degree of protection according to EN60529. Equipment: - during installation the frame stays attached via a safety hinge mechanism that prevents it from dropping down accidentally. - with wall mounting plate. - gasket in eco-friendly material. Mounting: can be installed on pole with acc. 96 Easy installation: equipped for wall mount.

Light output 1



1 x LCWJ-1282			
Nominal lamp power	9 W	LOR	100%
Lamp flux	1119 lm	Total flux	1119 lm
Luminous efficacy	124 lm/W	Total power	9 W
CCT	4000 K		
CRI	80		

Mounting mode

Wall mounted

Shape and measurements

Length: 16.10 in
Width: 13.39 in
Height: 13.43 in

Adjustability

Fixed

Design

Material impression: Aluminum

Electric

System power: 9 W
Appliance Class: I

Protection

IP: 65
IK: 07
Designation labels: CE