


Product data sheet

SUNRAY II 3000K 45° WEISS MATT
8-12519455
MOLTO LUCE




SUNRAY II LED EINBAUSTRALER aus Aluminium, weiß matt, ähnlich RAL 9003, Ausstrahlwinkel 45°, Lichtaustritt direkt, max. 350/500/700mA, IP44/IP20


Light output 1



1 x LED			
Nominal lamp power	28 W	LOR	100%
Lamp flux	2750 lm	Total flux	2750 lm
Luminous efficacy	98 lm/W	Total power	28 W
CCT	3000 K		
CRI	80		



1 x LED			
Nominal lamp power	20 W	LOR	100%
Lamp flux	1950 lm	Total flux	1950 lm
Luminous efficacy	98 lm/W	Total power	20 W
CCT	3000 K		
CRI	80		



1 x LED			
Nominal lamp power	14 W	LOR	100%
Lamp flux	1450 lm	Total flux	1450 lm
Luminous efficacy	104 lm/W	Total power	14 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling recessed

Electric

System power: 14-28 W
Appliance Class: II

Shape and measurements

Height: 3.19 in

Diameter: 5.51 in

Adjustability

Fixed

Design

Color of housing: White

Protection

IP: 20