


Product data sheet

VIGILANT LED HIGH BAY 24750 LUMENS, NARROW DISTRIBUTION, DIFFUSED ACRYLIC LENS
HEX3NC2EXXXXXN
DIALIGHT



Vigilant LED High Bay 24,750 Lumens 186 Watts 100-277V AC, 120-250V DC Cool White, 80CRI Diffused Acrylic Lens UL 1598/A (wet locations) CSA C22.2 No. 250 NEMA 4X CE, ENEC EN 60598-1:2015 EN 60598-2-1 (ed. 1), IEC 60598-2-1 (ed. 8) EN 60598-2-24:2013 EN 62471:2008, EN 62778:2014 EN 62493:2015 IEC60068 Salt Spray Testing - Severity 1 D-Marking to EN 60598 2-24 IK06 Narrow Distribution IP66/67 Scaled IES File

Light output 1 (integrated)



Lamp type	LED	CCT	5181 K
Nominal lamp power	186 W	CRI	80
Total flux	24751 lm	LOR	100%
Luminous efficacy	133 lm/W	Total power	186 W

Mounting mode

Pendant

Shape and measurements

Height: 3.00 in

Diameter: 15.96 in

Adjustability

Rotatable, Tilttable

Electric

System power: 186 W

Voltage: 240 V AC, 120 V AC, 277 V AC, 110 V AC, 230 V AC

Appliance Class: I

Protection

IP: 66

IK: 06