


# Product data sheet

MONDANA-A  
551092.002.1  
RZB




IP  
65

IK  
10

Series: Mondana Type of Protection: IP 65 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Base: plastic (polycarbonate), microtextured finish. Diffuser fastening: screw fitting. Diffuser: plastic (polyethylene), opal, satin finish. With Gore-TM Protective Vents membrane valve as standard. Available Colours: pure white (RAL 9010) Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 440, H 109 Lamp: LED Life time: 50000 h (L80/B50) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK10 (20 Joule) Luminaire flux LED: 1200lm System power: 13W Beam Angle: 113° Number of fittings B10A: 114 Number of fittings B16A: 182 Number of fittings C10A: 114 Number of fittings C16A: 182 Inrush current: 0,15A Unified Glare Ratio: 17,1 EEC: A+

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	13 W	CRI	80
Total flux	1200 lm	LOR	100%
Luminous efficacy	92 lm/W	ULOR	16%
		Total power	13 W

## Mounting mode

Wall mounted

## Shape and measurements

Height: 4.29 in  
Diameter: 17.32 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 13 W

## Protection

IP: 65  
IK: 10