Product data sheet


ECLDISPLAY
ECLDISPLAYCC_5600K_PROFILE2040_MAX ZOOM
PROLIGHTS



IP 20 IK 08

EclDisplay is a range of revolutionary and flexible LED spotlights designed for galleries, retail and any public venue where an advanced but classical looking fixture is needed, with several control options, sources and optic versions available to precisely meet any application. The EclDisplay CC is the version of the EclDisplay range made to be connected to an external Constant Current PSU and driver (max 700mA/36V), selecting among the PROLIGHTS accessories or any third-party compatible component, leaving to System Integrators to install this luminaire in venues with their own wiring distribution and control. The EclDisplay CC includes a high-efficiency 25 W White, high CRI LED source, available in 2.700 K, 3.000 K, 4.000 K, 5.600 K variants, and it is completed with a wide selection of optional zoomable profile or wash lenses, and other optical accessories like louvres and snoots, making it truly a multi-purpose fixture. Features: Constant Current version to be connected to external PSU and driver (max 700mA/36V) 25W high CRI White LED available in 2.700 K, 3.000 K, 4.000 K, 5.600 K versions, both black and white housing Multiple lens options: zoomable profile or wash optics

Light output 1



1 x LED

Nominal lamp power	34.9 W	LOR	100%
Lamp flux	1869 lm	Total flux	1873 lm
Luminous efficacy	54 lm/W	Total power	40 W
CCT	5817 K		
CRI	90		

Mounting mode

Ceiling mounted, Contact rail, Standing / Bollard

Shape and measurements

Length: 4.87 in
Width: 3.35 in
Height: 7.45 in

Adjustability

Rotatable, Tiltable, Free

Electric

System power: 40 W
Controller: DMX, DALI
Color adjustable
Appliance Class: I

Protection

IP: 20
IK: 08
Surface temperature: 65°C
Designation labels: CE