


Product data sheet

LIGHTING FOR ADMINISTRATIVE AND OFFICE BUILDINGS
V1-A0-00300-010P0-4007050 A300 2.0 IP40 1195X595X50 MM 70W 5000K OPAL
VARTON




IP
40

IK
03

Versatile office luminaire. Stainless steel housing with white powder coating. Application: administrative facilities, lobbies. Recessed and surface-mounted. Compatible with the Armstrong Prelude 24 suspended ceiling systems. Input voltage (AC, 50Hz): 176...264 AC frequency: 50 Flicker: 1 Climatic modification and category of placement: YXL4 Height/depth: 50 Length: 1 195 Protection class: I Ingress protection (IP): IP40 Impact resistance: IK03 Width: 595 Power factor: 0,95 <https://www.varton.ru/products/ofisnoe-osveshchenie/a-seriya-2-0/a300-2-0-ip40-ofis-1195-595-analog-4-36/svetodiodnyy-svetilnik-var-ton-a300-2-0-ofisnyy-70-vt-vstraivaemyy-nakladnoy-5000-k-1195-595-50-mm-ip/>

Light output 1



1 x LED			
Nominal lamp power	70 W	LOR	100%
Lamp flux	8960 lm	Total flux	8961 lm
Luminous efficacy	128 lm/W	Total power	70 W
CCT	5000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 47.05 in

Width: 23.43 in

Height: 1.97 in

Adjustability

Fixed

Electric

System power: 70 W

Protection

IP: 40

IK: 03