Product data sheet


APOLLO G2 CITYLINE FSW 1260MM PO 1X20.46W 065° 2924LM
9380B19T
PRACHT



IP 65 IK 06

DB-listed Reflector luminaire APOLLO G2 Cityline FSW 1260mm PO 1x20.46W 065° 2924lm 4.000K, class II, with TW 5x2,5mm²+2x1,5mm², Protective conductor only, overvoltage protection, inrush current limiter. New generation of the APOLLO damp-proof reflector luminaire. DB listed and class II CRI>90. Ideal for ceiling and wall mounting. 5 years warranty. Item number: 9380b19t GTIN: 4018098446996 Technical details/specification: Cover made of PO; Housing made of GRP polyester white; 220–240 V 50/60 Hz; Energy efficiency class D; Number of light sources / LED rows: 1; IP65; Through-wiring in mm²: 5x2,5+2x1,5; Dimensions: LxWxH: 1260mm x 105mm x 152mm; Diameter: mm

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	20 W	CRI	90
Total flux	2924 lm	LOR	100%
Luminous efficacy	146 lm/W	Total power	20 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 49.61 in
Width: 4.13 in
Height: 5.98 in
Weight: 3 kg

Adjustability

Tiltable

Electric

System power: 20 W
Appliance Class: II

Protection

IP: 65
IK: 06

Other operating numbers

Ambient temperature range: -13...113°F