
Product data sheet


LED DOWNLIGHTS
V1-R0-90252-20L20-2001040 DL-BOX REFLECT MULTI 1X4 LOW 10W 4000K
VARTON



IP 20 IK 01

Input voltage (AC, 50Hz), V: 198...264 AC frequency, Hz: 50 Flicker, %: 1 Climatic modification and category of placement: УХЛ4 Protection class: II Housing material: Aluminium Mounting method: Surface mounting Ingress protection (IP): IP20 Impact resistance: IK01 Power factor: 0,95 https://www.varton.ru/products/daunlayty/dl-box-reflect/dl-box-reflect-multi-1x4-low/svetodiodnyy-svetilnik-varton-dl-box-reflect-multi-10-vt-1x4-nakladnoy-4000-k-150kh40kh115-mm-ral900_1/

Light output 1



1 x LED

Nominal lamp power	10 W	LOR	100%
Lamp flux	1000 lm	Total flux	1000 lm
Luminous efficacy	100 lm/W	Total power	10 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 5.91 in
Width: 1.57 in
Height: 4.53 in

Adjustability

Fixed

Electric

System power: 10 W

Protection

IP: 20
IK: 01