


# Product data sheet

PRO-STRADA MINI, 30LEDS OPTIEK 1  
 41362X0X  
 PROLUMIA




Light Source: Cree / Lumileds / Samsung / Osram Color temperature: 3000K / 4000K Color rendering index: Ra ≥ 70 Operating temperature: -30°C ~ +50°C Rated life hours: L90 > 100.000 hours 300-500mA LED driver (included): Philips Xitanium SR programmable / 1-10V / Dali Input: 220-240V AC 50/60Hz Power factor: > 0,95

## Light output 1




### 1 x LED

Nominal lamp power	27.2 W	LOR	100%
Lamp flux	3800 lm	Total flux	3800 lm
Luminous efficacy	140 lm/W	Total power	27.2 W
CCT	4000 K		
CRI	80		




### 1 x LED

Nominal lamp power	28.7 W	LOR	100%
Lamp flux	3800 lm	Total flux	3800 lm
Luminous efficacy	132 lm/W	Total power	28.7 W
CCT	3000 K		
CRI	80		



### 1 x LED

Nominal lamp power	24.1 W	LOR	100%
Lamp flux	3200 lm	Total flux	3200 lm
Luminous efficacy	133 lm/W	Total power	24.1 W
CCT	4000 K		
CRI	80		



**1 x LED**

Nominal lamp power  
Lamp flux  
Luminous efficacy  
CCT  
CRI

25.5 W  
3200 lm  
125 lm/W  
3000 K  
80

LOR  
Total flux  
Total power

100%  
3200 lm  
25.5 W

**Mounting mode**

Ceiling mounted, Pole top mounted

**Shape and measurements**

Length: 22.87 in  
Width: 12.09 in  
Height: 4.25 in

**Electric**

System power: 24.1-28.7 W  
Appliance Class: 0

**Protection**

IP: 66  
IK: 08  
Designation labels: CE, ENEC