


# Product data sheet

SL720LED SLL 66 S/C 8TW GR9006 HCL MP  
8720761779930  
PERFORMANCE IN LIGHTING



LED free-standing luminaire for interior, including: Steel sheet head, extruded aluminium profile post, steel sheet base, powder painted / Angle of the lamp head adjustable using a set screw / Micropismatic diffuser for efficient light diffusion, glare reduction and a high uniformity / Direct / indirect light distribution / Colour rendering index Ra > 80 / Colour tolerance according to MacAdam = 3 SDCM / Direct share of light dimmable, colour temperature 4000K / Complete with flexible power cord with plug / VDU application suitable acc. to EN 12464-1 / Light colour and brightness of indirect light share manually adjustable via Tunable White control / Light colour and brightness of indirect light share automatically adjustable via HCL (Human Centric Lighting) for wholesome and performance-enhancing management of the biorhythm / 3000 K colour temperature version on demand / Special colour versions available upon request

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 4000 K |
| Nominal lamp power | 70 W     | CRI         | 80     |
| Total flux         | 10469 lm | LOR         | 100%   |
| Luminous efficacy  | 150 lm/W | ULOR        | 84%    |
|                    |          | Total power | 70 W   |

## Mounting mode

Standing / Bollard

## Shape and measurements

Length: 27.76 in

Width: 16.93 in

Height: 81.77 in

## Design

Color of housing: Silver gray

## Electric

System power: 70 W

Appliance Class: I

## Protection

IP: 20