


Product data sheet

SL720LED SLL 66 S/C 8TW GR9006 HCL MP
8720761779930
PERFORMANCE IN LIGHTING



LED free-standing luminaire for interior, including: Steel sheet head, extruded aluminium profile post, steel sheet base, powder painted. Angle of the lamp head adjustable using a set screw. Microprismatic diffuser for efficient light diffusion, glare reduction and a high uniformity. Direct-indirect light distribution. Colour rendering index Ra > 80. Colour tolerance according to MacAdam = 3 SDCM. Direct share of light dimmable, colour temperature 4000K. Complete with flexible power cord with plug. VDU application suitable acc. to EN 12464-1. Light colour and brightness of indirect light share manually adjustable via Tunable White control. Light colour and brightness of indirect light share automatically adjustable via HCL (Human Centric Lighting) for wholesome and performance-enhancing management of the biorhythm. 3000 K colour temperature version on demand. Special colour versions available upon request.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	70 W	CRI	80
Total flux	10469 lm	LOR	100%
Luminous efficacy	150 lm/W	ULOR	5%
		Total power	70 W

Mounting mode

Standing / Bollard

Shape and measurements

Length: 27.76 in
Width: 16.93 in
Height: 81.77 in

Design

Color of housing: Silver gray

Electric

System power: 70 W
Appliance Class: I

Protection

IP: 20