
# Product data sheet

Z44 CE L1200 29W 4500 DALI KOOLMESH MW 840 51388405137

**AURA LIGHT** 










Z44 is a versatile luminaire for general lighting in locations requiring protection class up to IP44. The efficient frosted prismatic diffuser offers exceptional uniformity, while safeguarding against glare. The modern and slim design of the luminaire minimizes packaging materials and makes the Z44 very transportation efficient, further contributing to the sustainability of the solution. Z44 can be ordered with built-in HF sensor. The sensor ensures that the light is on only when required. Easy to use settings of detection range and delay time. There are three different sensor-versions: On/off. Profile 1 with 100 % light when presence is detected and 10% light at no detection, "High-low". Profile 2 with 100% light when presence is detected, then 10% light for 30 minutes, then the luminaire turns off, "High-Low-Off". Emergency versions with 3h built-in battery-pack. Through-wiring versions on request.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	29 W	CRI	80
Total flux	4670 lm	LOR	100%
Luminous efficacy	161 lm/W	ULOR	5%
		Total power	29 W

## Mounting mode

Ceiling mounted

# Shape and measurements

Length: 46.93 in Width: 6.93 in Height: 2.36 in

#### Adjustability

Fixed

#### Electric

System power: 29 W Appliance Class: I

### Protection

IP: 44 IK: 03