# Product data sheet


LINA45-S 145S-2C0I-25GEM3/840, B
145S-2C0I-25GEM3/840
HALLA



IP 20


145S-2C0I-25GEM3/840, B Luminaire surface Material of luminaire: Colour of luminaire: Shape of luminaire: Linear Size: 1403 x 47 x 69 mm Type of installation: Surface Distribution: Direct Optics type: Microprisma Protection class: I Voltage: 220-240V

## Light output 1 (integrated, emergency)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 1.5 W | CRI | 80 |
| Total flux | 260 lm | LOR | 100% |
| Luminous efficacy | 173 lm/W | Total power | 1.5 W |

## Light output 2 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 10.9 W | CRI | 80 |
| Total flux | 1610 lm | LOR | 100% |
| Luminous efficacy | 148 lm/W | Total power | 10.9 W |

### Mounting mode

Ceiling mounted

### Shape and measurements

Length: 1.85 in
Width: 55.24 in
Height: 2.72 in

### Adjustability

Fixed

### Electric

System power: 12.4 W
Appliance Class: I

### Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

### Protection

IP: 20