Product data sheet

VEKTER 13 STREET AND AREA LIGHTING LUMINAIRES VK-20012-T2-W40

LIGMAN











- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear, impact-resistant, toughened glass diffuser - Maximum wind load resistance is 140 km/h - Surge protection 10 kV

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	28 W	CRI	80
Total flux	3114 lm	LOR	100%
Luminous efficacy	111 lm/W	Total power	28 W

Light output 2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	28 W	CRI	80
Total flux	3114 lm	LOR	100%
Luminous efficacy	111 lm/W	Total nower	28 W

Mounting mode

Pole integrated, Pole top mounted

Shape and measurements

Length: 27.40 in Width: 10.24 in Height: 13.39 in Weight: 56.2 kg

Adjustability

Free

Glare protection

Glare protection: UGR < 19

Electric

System power: 56 W Voltage: 230 V AC Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Design

Color of housing: Black, White, Silver gray

Protection

IP: 65

IK: 08

Surface temperature: 40°C