


# Product data sheet

SLOIN TW E SL LED3800-830-60 L2250 PC  
42184141  
ZUMTOBEL



LED light line with DALI-controllable LED converter, with cover to 50m from one piece; LED service life lasts 50000 h before luminous flux is reduced to 90% of the initial value. Chromaticity tolerance (initial MacAdam): 3. Luminaire luminous flux: 4065 lm, Luminaire efficacy: 58 lm/W. Colour rendering Ra > 80, colour temperature 3000 K to 6000K. Luminaire of sheet steel, white enamelled. Luminaire with completely uniform appearance due to polycarbonate cover. Luminaire consists of housing and continuous optic of polycarbonate. Includes gear tray, wiring, and end-cap set. Luminaire wired with halogen-free leads and covers are due to norm classified as TP(a). Degree of protection: IP54 (IP20 on ceiling side). Dimensions: 2250 x 72 x 136 mm weight: 7.25 kg

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	70 W	CRI	80
Total flux	4065 lm	LOR	100%
Luminous efficacy	58 lm/W	Total power	70 W

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 88.58 in  
Width: 2.83 in  
Height: 5.35 in  
Weight: 7.3 kg

## Design

Color of housing: White

## Electric

System power: 70 W  
Voltage: 220-240 V AC  
Controller: DALI  
Appliance Class: I

## Protection

IP: 20  
IK: 07  
Designation labels: CE, ENEC