

Product data sheet

GUSTAV I (1-ARMED)
9.681.3162.07
LEIPZIGER LEUCHTEN



IP
55


Mounting height of 3.00 to 4.50 m for medium light requirements - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Mirror lamellae for light guidance and glare limitation made of premium highest-grade aluminium, burnished and anodized - Aluminium reflector finished in special white paint for max. light reflection - Aluminium cover painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components arranged on a block - Connection with adapter jack - Available in any RAL or DB colour without surcharge - Order pole, dia. 76 mm, separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure mercury vapour lamp

Nominal lamp power	125 W	LOR	54%
Lamp flux	6800 lm	ULOR	11%
Luminous efficacy	27 lm/W	Total flux	3648 lm
CCT	3400 K	Total power	137 W
CRI	54		



1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	54%
Lamp flux	4000 lm	ULOR	11%
Luminous efficacy	24 lm/W	Total flux	2146 lm
CCT	3400 K	Total power	89 W
CRI	54		

Mounting mode

Pole top mounted

Shape and measurements

Height: 29.13 in
Diameter: 9.84 in

Electric

System power: 89-137 W

Protection

IP: 55