Product data sheet

LUNAOP 40003/4000/CU MARTINELLI LUCE





1 x LED


Lamp flux

Nominal lamp power

Luminous efficacy

A ring of light, slight suspended in the space, designed to provide a minimal visual impact. An exterior frame in white lacquered aluminum highlights its profile and an inner white opal methacrylate band ensures an optimal diffusion light with LED source. dimmable drivers integrated into the ceiling support.

Light output 1




	CCT	4000 K	Total power	103 W
	CRI	80		
\searrow	1 x LED			
$\langle \rangle$	Nominal lamp power	103 W	LOR	100%
H	Lamp flux	7150 lm	ULOR	36%
H	Luminous efficacy	69 lm/W	Total flux	7150 lm
	CCT	3000 K	Total power	103 W
T.	CRI	80		

103 W

4415 lm

41 lm/W



k LED			
ominal lamp power	103 W	LOR	
mp flux	7150 lm	ULOR	
iminous efficacy	69 lm/W	Total flux	
CT	3000 K	Total power	
31	80		

LOR

ULOR

Total flux

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 47.24 in Width: 47.24 in Height: 2.56 in Weight: 5.5 kg

Adjustability

Tiltable, Height adjustable

Electric

System power: 103 W Controller: DALI Appliance Class: I

Protection

IP: 20 Surface temperature: 230°C 100%

36%

4415 lm

Design

Material impression: Aluminum Color of housing: White Designer: emiliana martinelli