


# Product data sheet

LOUI 50  
925361.0045.76  
RZB




IP  
20

IK  
03

Series: LESS IS MORE 50system Gerades Einbaumodulgehäuse Aluminium-Strangpressprofil pulverbeschichtet, stirnseitig offen zum weiter verdrahten zum Lichtbandsystem für Montage in Zwischendecken oder Leichtbau-Hohlwände. Austauschbare und herausnehmbare LED-Einheit mit integriertem Betriebsgerät. Alea Optik System: Reflektorstruktur (ABS, Aluminium bedampft, hochglänzend) mit Diffusor aus vergilbungsfreiem Kunststoff (PMMA) opal für blendfreies Licht am Arbeitsplatz (UGR <19, Bildschirmgerecht gemäß DIN EN 12464-1). Colour: silver, matt (approx. RAL9006) Length: 1121mm Width: 71mm Height: 1.5mm Cut-out length: 1128mm Cut-out width: 60mm Recess height: 100mm Luminaire: recess height: 75mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 System power: 28W Rated luminous flux: 3350lm Luminous efficiency: 120lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP20

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 3000 K |
| Nominal lamp power | 28 W     | CRI         | 80     |
| Total flux         | 3350 lm  | LOR         | 100%   |
| Luminous efficacy  | 120 lm/W | Total power | 28 W   |

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 2.80 in  
Width: 44.13 in  
Height: 0.08 in

## Adjustability

Fixed

## Electric

System power: 28 W

## Protection

IP: 20  
IK: 03