


# Product data sheet

CYBERIA FX 371.LED 840 22700LM 210W IP65 RAL9005 DRV DIM DALI  
5797265L60S  
ES-SYSTEM



Oprawa nastropowa lub zwieszana OBUDOWA: aluminiowa, lakierowana, ramka w kolorze białym RAL 9016 DYFUZOR: szkło hartowane lub laminowane, przezroczyste dostępne na zamówienie OPTYKA: wysokowydajne panele soczewkowe, 3 rozsyły światłości 60°, 90°, 30°x70° ZASILACZ: elektroniczny, na zewnątrz oprawy INNE: akcesoria zamawiane oddzielnie HOUSING: painted aluminum, white RAL 9016 frame DIFFUSER: transparent hardened or laminated glass, available upon request OPTICS: 3 light distribution variants: 60°, 90° and 30°x70° POWER SUPPLY: remote electronic power supply OTHER: accessories to be ordered separately GEHÄUSE: Aluminium, lackiert, RAL 9016 weißer Rahmen DIFFUSOR: Glas gehärtet oder laminiert, transparent, auf Anfrage erhältlich OPTIK: 3 Lichtverteilungsvarianten: 60°, 90° und 30°x70° STROMVERSORGUNG: elektronisch, außerhalb der Leuchte SONSTIGES: Zubehör separat zu bestellen

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 4000 K |
| Nominal lamp power | 210 W    | CRI         | 80     |
| Total flux         | 22700 lm | LOR         | 100%   |
| Luminous efficacy  | 108 lm/W | Total power | 210 W  |

## Mounting mode

Pendant

## Shape and measurements

Length: 14.57 in  
Width: 14.57 in  
Height: 8.07 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 210 W  
Voltage: 230 V AC  
Ballast: ECG  
Controller: DALI  
Appliance Class: I

## Protection

IP: 65  
IK: 09