

Product data sheet

DECORATIVE LIGHTING

V1-R0-9Q503-30D01-2007030 COSMO Q 900X900 SUSPENDED 70W 3000K DALI

VARTON




IP
40

IK
03

• Square luminaire with homogenous illumination and smooth angles • Material: Stainless steel housing Application • Offices • Corridors • Lobbies • Reception areas • Hospitality (restaurants, hotels, coffee bars) Installation • Suspended Input voltage (AC, 50Hz), V: 220...240 AC frequency, Hz: 50 Flicker, %: 5 Climatic modification and category of placement: YXJ4 Protection class: I Housing material: Aluminium Mounting method: Pendant Ingress protection (IP): IP40 Impact resistance: IK03 Power factor: 0,95 https://www.varton.ru/products/interernoe-dekorativnoe-osveshchenie/cosmo-q/cosmo-q-900x900-podvesnye/svetodiodnyy-svetilnik-varton-cosmo-q-900kh900kh115-mm-70-vt-podvesnoy-cri90-3000-k-ra19005-chernyy-_1/

Light output 1



1 x LED			
Nominal lamp power	70 W	LOR	100%
Lamp flux	7600 lm	Total flux	7601 lm
Luminous efficacy	109 lm/W	Total power	70 W
CCT	3000 K		
CRI	90		

Mounting mode

Pendant

Shape and measurements

Length: 35.43 in

Width: 35.43 in

Height: 4.53 in

Adjustability

Fixed

Electric

System power: 70 W

Protection

IP: 40

IK: 03