Product data sheet


TRIONA OPAL
312394.0031
RZB



IP 20

Series: Triona Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Deckenbaldachin (D 260 mm, H 40 mm) Aluminium eloxiert. Mit Verbindungsleitung zwischen Leuchte und Deckenbaldachin. Mit 3-Punkt-Stahlseilabhängung, stufenlos höhenverstellbar. Leuchtenrahmen Metall pulverbeschichtet. Diffusorsegmente (Lichtaustritt indirekt) aus vergilbungsfreiem Kunststoff (PMMA) opal. Diffusor (Lichtaustritt direkt) aus Kunststoff (PMMA) opal. Betriebsgerät eingebaut. Leuchtmittel (LED) im Lieferumfang enthalten. Available Colours: anthracite metallic Type of Installation: Pendant Dimensions: D 1009, H 52 Lamp: LED Life time: 50000 h (L70/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Luminaire flux LED: 11300lm System power: 122W Beam Angle: 104° Number of fittings B10A: 4 Number of fittings B16A: 6 Inrush current: 106A Unified Glare Ratio: 18,4 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	122.4 W	CRI	80
Total flux	11300 lm	LOR	100%
Luminous efficacy	92 lm/W	ULOR	27%
		Total power	122.4 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 2.05 in
Diameter: 39.72 in

Adjustability

Fixed

Electric

System power: 122.4 W

Protection

IP: 20