


Product data sheet

CONTENDER LED 5K LUMEN NEMA TYPE V 5000 K CCT
I/VMV5LCD5BU
APPLETON (EMERSON EGS)



Contender LED Luminaire Series Retrofit Diffused Polycarbonate Globe NEMA Type V Symmetrical 5000 K CCT/ 70 CRI Voltage- BU-120-277V, 50/60Hz, 125-300 Vdc BH-347-480 Vac, 50/60Hz Class I, Division 2, Groups A, B, C, D Class I, Zone 2, IIC Zone 21, IIIC Class I, Zone 2, IIC Class II, Division 1, Group F, G Class II, Division 2, Group F, G Class III Simultaneous Exposure Type 3R, 4,4X IP66/IP67 Suitable for Use in Wet Locations Marine Outside Type (Salt Water) ABS Certified DLC Qualified Product listed Refer to catalog for additional options

Light output 1 (integrated)



Lamp type	LED	CCT	5181 K
Nominal lamp power	47 W	CRI	70
Total flux	5199 lm	LOR	100%
Luminous efficacy	111 lm/W	Total power	47 W

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Height: 1.00 in
Diameter: 7.50 in

Adjustability

Fixed

Electric

System power: 47 W
Appliance Class: II

Protection

IP: 67
Explosion zone suitability: 2, 21