


Product data sheet

VRT3 L295 OA E3
VERTECO3 EMERGENCY
DEXTRA




Verteco 3 - IP20 Industrial Luminaire with open area optics. Steel body white powder coated paint finish and green polycarbonate end caps. Mounting to lighting trunking using standard 20mm brass bush and locknut assembly. Side entry panel mount with female power feed plug supplied. Options: E3 - Emergency control gear (1056 lumens output) ST3 - Emergency Selftest AT3 - Emergency Autotest R18U - Reacta 18 Ultra-Wide, Presence & Daylight Detection R18H - Reacta 18, Daylight and Presence Detection Sensor, Narrow Lens R18W - Reacta 18, Daylight and Presence Detection Sensor, Wide Lens R18HRF - Reacta 18, Daylight and Presence Detection Sensor, Wireless Version, Narrow Lens R18WRF - Reacta 18, Daylight and Presence Detection Sensor, Wireless Version, Wide Lens RLS10 - Reacta-Link Wireless Presence 10M RLS15 - Reacta-Link Wireless Presence 15M RCS - Reacta-Control Wireless, Presence

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	179.9 W	CRI	80
Total flux	27168 lm	LOR	100%
Luminous efficacy	151 lm/W	ULOR	4%
		Total power	179.9 W

Light output 2 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3.98 W	CRI	80
Total flux	792 lm	LOR	100%
Luminous efficacy	199 lm/W	ULOR	4%
		Total power	3.98 W

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 59.37 in
Width: 8.46 in
Height: 3.31 in

Electric

System power: 183.88 W
Ballast: ECG

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Adjustability

Fixed

Protection

IP: 20

Designation labels: CE