# Product data sheet


LEVIDO SWING ROUND
901835.002.2.76
RZB



IP 40 IK 06


Series: LEVIDO SWING round Round recessed projector with very small dimensions. Die-cast aluminium cover, powder-coated. Extruded aluminium heat sink. Reflector: aluminium, highly polished anodised finish. With safety glass. Can be swivelled by ± 25°. Medium beam light distribution. Light beam 23°. MultiLumen: Luminous flux adjustable in 2 steps. Factory-set to maximum luminous flux. Suitable for Recessed ceiling mounting. Luminaire mounting with spring system. Including separate LED converter with connecting cable 250 mm. Suitable for through-wiring. Opal diffuser (PMMA) for uniform, homogenous light distribution available as an accessory. Colour: traffic white, matt (RAL 9016) Diameter: 91 mm Height: 2 mm Cut-out diameter: 78 mm Recess height: 80 mm Luminaire: recess height: 80 mm Lamp: LED Socket: without socket Colour temperature: 2700K Colour rendering index (CRI): 80 System power: 7.5 W Rated luminous flux: 650 lm Beam angle Down: 23° Luminous efficiency: 87 lm/W System power 2: 12 W Rated luminous flux 2: 1000 lm Luminous efficiency 2: 83 lm/W Control gear: Converter, dimmable, DALI Protection class: II Type of protection: IP 40

## Light output 1



1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 7.5 W | LOR | 67% |
| Lamp flux | 650 lm | ULOR | 14% |
| Luminous efficacy | 58 lm/W | Total flux | 434 lm |
| CCT | 2700 K | Total power | 7.5 W |
| CRI | 80 | | |



1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 12 W | LOR | 67% |
| Lamp flux | 1000 lm | ULOR | 14% |
| Luminous efficacy | 56 lm/W | Total flux | 667 lm |
| CCT | 2700 K | Total power | 12 W |
| CRI | 80 | | |

### Mounting mode

Ceiling recessed

### Shape and measurements

Height: 0.08 in
Diameter: 3.58 in

### Electric

System power: 7.5-12 W

### Protection

IP: 40
IK: 06

### Adjustability

Rotatable, Tiltable

### Design

Color of housing: White