


Product data sheet

QUANTUM 1 FLOODLIGHTS,PROJECTORS
QA-50004-M-40
LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour RGBW 30, 40 - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Through wiring on request - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency optical reflector or PMMA lens - Clear toughened glass - Integral control gear

Light output 1 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	9.2 W	CRI	80
Total flux	507 lm	LOR	100%
Luminous efficacy	55 lm/W	Total power	9.2 W

Light output 2 (integrated)




Lamp type	LED	CCT	0 K
Nominal lamp power	9.3 W	CRI	-50
Total flux	72 lm	LOR	100%
Luminous efficacy	8 lm/W	Total power	9.3 W

Light output 3 (integrated)



Lamp type	LED	CCT	7247 K
Nominal lamp power	9.3 W	CRI	-18
Total flux	496 lm	LOR	100%
Luminous efficacy	53 lm/W	Total power	9.3 W

Light output 4 (integrated)



Lamp type	LED	CCT	0 K
Nominal lamp power	6.9 W	CRI	-29
Total flux	286 lm	LOR	100%
Luminous efficacy	41 lm/W	Total power	6.9 W

Mounting mode

Standing / Bollard, Wall mounted

Shape and measurements

Height: 12.13 in
Diameter: 7.09 in
Weight: 3.7 kg

Adjustability

Free

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 34.7 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 66
IK: 08
Surface temperature: 40°C