

Product data sheet

DECORATIVE LIGHTING
V1-R0-00713-30000-4055040 COSMO 2500 MM SUSPENDED 550W 4000K
VARTON




IP
40

IK
03

• Round luminaire with homogenous illumination • Material: Stainless steel housing Application • Offices • Corridors • Lobbies • Reception areas • Hospitality (restaurants, hotels, coffee bars) Installation • Suspended Input voltage (AC, 50Hz): 220...240 AC frequency: 50 Flicker: 5 Climatic modification and category of placement: УХЛ4 Protection class: I Housing material: Aluminium Mounting method: Pendant Ingress protection (IP): IP40 Impact resistance: IK03 Power factor: 0,95 <https://www.varton.ru/products/interernoe-dekorativnoe-osveshchenie/cosmo/cosmo-2500-mm-podvesnye/svetodiodnyy-svetilnik-var-ton-cosmo-podvesnoy-550-vt-cri90-2500kh100-mm-4000-k-s-rasseivatelem-opal-/>

Light output 1



1 x LED			
Nominal lamp power	550 W	LOR	100%
Lamp flux	40700 lm	Total flux	40707 lm
Luminous efficacy	74 lm/W	Total power	550 W
CCT	4000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Height: 3.94 in
Diameter: 98.43 in

Adjustability

Fixed

Electric

System power: 550 W

Protection

IP: 40
IK: 03