


Product data sheet

VARIATIC LED RECESSED LUMINAIRE, OPAL COVER
VA3102100-73-40
SCHMITZ | WILA



Variatic LED 4000 K Recessed Luminaire, Light distribution direct Opal Cover Luminaire housing stainless steel (V2A) Product: VA3102100-73-40 Light Technique Direct light distribution through opal cover CRI > 80 Colour temperature 4000 K Lifetime 50.000 h (L70) Luminaire housing Luminaire housing made of brush-finished stainless steel (V2A) End caps fitted without visible screw connection Opal cover made of PMMA satinated and scrtch resistand surface Operating and assembly technology LED driver directly integrated, standard Suitable for emergency lighting with central battery Plug-in terminals for through wiring up to 3 x 2.5mm² Simple mounting with adjustable recessed brackets for ceiling thicknesses 1-35 mm Lamp Wattage: 31 W Colour Rendering Index: 80 Colour Temperature: 4000 K Luminaire Luminous Flux: 2840 Llm System Efficiency: 77 Llm/W Luminance $\gamma \geq 65^\circ$: --- UGR: 23 Number Luminaires LZ: 0.05 Connector: Steckklemmen, 3 x 2,5 mm² Length: 1150 mm Width: 120 mm Cut-out length: 1135 mm Cut-out width: 108 mm Installation Depth RD: 95 mm Total Weight: 4.2 kg Degree of Protection IP20 CE-Sign Total system: Protection class 1 Data record VA3102100-73-40

Light output 1



1 x General service incandescent lamp			
Nominal lamp power	37 W	LOR	100%
Lamp flux	2840 lm	Total flux	2840 lm
Luminous efficacy	77 lm/W	Total power	37 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 45.28 in
Width: 4.72 in
Height: 3.74 in

Adjustability

Fixed

Electric

System power: 37 W
Appliance Class: I

Protection

IP: 20