

Product data sheet


URBINO TWILIGHT LED 27W 3100LM 3000K IP66 O3 - FOR LOCAL ROADS GRAY II
130222.5L422.021.986

LUG



Professional streetlight luminaire for LED light sources. Luminaire with twilight sensor. High efficacy to 131 lm/W Mounting: on pillar $\varnothing 60/76$ mm, on outriggers $\varnothing 60/76$ mm Body: high pressure die-cast aluminum Lateral Surface Wind Exposed: 0.054 m² Power supply efficiency >95% Power: 220-240V 50/60Hz Lifetime (L90B10): 100 000 h Available on request: DALI, DIM 1..10V, LLOC, knife switch, 10kV surge protection, NTC, access to the driver chamber without the use of tools. Additional information: tilt adjustment: -15° to +15° (every 5°). Other remarks: the pole and boom are not part of the luminaire Warranty: 5 years Application: express roads, local roads, town roads, residential area roads, pedestrian crossings, area lighting, avenues, promenade, cycle paths. Type of optics: O3 - for local roads

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	27 W	CRI	70
Total flux	3100 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	27 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 21.65 in

Width: 9.84 in

Height: 7.68 in

Adjustability

Tiltable

Design

Color of housing: Silver gray

Electric

System power: 27 W

Appliance Class: II

Integrated sensors

Integrated sensors: Daylight sensor

Protection

IP: 66

IK: 08