
Product data sheet

SASKIA I DA LED (OPTIC 268) 9.215.8107.65268A LEIPZIGER LEUCHTEN



total height: 3.50m (other heights on request) light standards: low and medium lighting requirements lamp: incl. 1 or 2 DA LED modules; easy to replace colour temperature: 4.000K neutral white or 3.000K warm white (other colour temperatures on request) surge protection: 10kV LED gear: incl. driver, up to 100,000 hours; with integrated Constant Light Output (CLO) in order to keep the luminous flux at the same level over the entire life time; AC/DC compatible for emergency LED life expectancy: 65,000 hours/ L100/ B10; 100,000 hours/ L90 /B10 for minimum maintenance costs due to an excellent thermal management light control: at extra cost: power reduction, dimming, DALI or CLEVER LIGHT optical system: directed light (multi layer) provided by an exchangeable, anti-aging lens technology light distribution: street optics, square optics, area optics, cycle path optics, pedestrian crossing optics – other optics on request luminaire body: with 1 bracket, made of rectangular aluminium profile, with access door for cable junction box; powder coated colour: DB 703; other RAL or DB colour without extra cost on request glazing: flat, clear toughened glass glazing wiring: completely wired; incl. cable until access door installation: with flange plate to be screwed on a concrete foundation on site or on an additional bolt-on root or with root to be set into the ground accessory: cable junction box, bolt-on root with screws – to be ordered separately application areas: parkways, private areas, small squares, boulevards, schools, home for elderly people, hotels, factory premises, main streets, residential and local distributor roads, squares, parks, pedestrian zones, car parks

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	8 W	CRI	70
Total flux	964 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	8 W

Mounting mode

Pole integrated

Shape and measurements

Length: 25.59 in Width: 6.30 in Height: 4.72 in Weight: 44 kg

Adjustability

Height adjustable

Electric

System power: 8 W

Protection

IP: 65