Product data sheet


GSUN 3
652517.002
RZB



IP 54 IK 03


Series: GSUN 3 Luminaire for escape route identification. Base: plastic Diffuser: plastic, opal 4 plastic foils with escape route motifs included (ISO 7010). Suitable for Wall (surface). Electronic ballast included. Self-contained system with automatic self-test. smart+IP: NFC interface for quick and easy wireless configuration of operating parameters. Even before installation, the luminaire can be conveniently adjusted without voltage using the smart+IP app via NFC. Factory setting is to 3h, maintained power mode, automatic self-test. Configuration app for Android for download free of charge. Colour: white Length: 241 mm Width: 126 mm Height: 76 mm Weight: 360 g Operating mode: maintained power mode Viewing Distance: 21 m Duration time: 1 h, 3 h, 8 h Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 3.2 W Rated luminous flux: 160 lm Luminous flux, emergency: 150 System power, emergency: - Luminous flux, emergency 2: 100 lm System power, emergency 2: - Luminous flux, emergency 3: 40 lm System power, emergency 3: - Control gear: EB Protection class: II Type of protection: IP 54

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3.2 W	CRI	80
Total flux	160 lm	LOR	100%
Luminous efficacy	50 lm/W	ULOR	15%
		Total power	3.2 W

Light output 2 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3.2 W	CRI	80
Total flux	150 lm	LOR	100%
Luminous efficacy	47 lm/W	ULOR	15%
		Total power	3.2 W

Mounting mode

Wall mounted

Electric

System power: 6.4 W

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Shape and measurements

Length: 4.96 in

Width: 9.49 in

Height: 2.99 in

Adjustability

Fixed

Protection

IP: 54

IK: 03