Product data sheet


JUNISTAR LUX SQUARE WHITE 2X 1180LM 3000K RA 98 TRAILING EDGE DIMMING
7021989025917
SG ARMATUREN



IP 44

Single or double downlight for indoor use. Junistar Lux Square emits a harmonious, flicker-free light with excellent colour rendering. Its patented, adjustable 30-degree tilt function in all directions is covered by a 10-year warranty. It is available with a new switch box that provides better traction relieffor several types of cables, as well as bigger switch compartments and fittings for plastic tubing. Light distribution Direct Light technic LED (not exchangeable) 17W 3000K Ra 98 SDCM 1 L90/B10 >100,000 hrs Control/Dimming Trailing edge dimming Protection Class II SELV IP44 Materials and finish Housing: Aluminium Colour: White (RAL 9003, 25% gloss) Optics: Tempered glass Mounting/Connection Recessed, Indoor Screwless terminal block Max. luminaires per circuit breaker: B10: 52, B16: 84, C10: 52, C16: 84

Light output 1



1 x LED

Nominal lamp power	17 W	LOR	100%
Lamp flux	1180 lm	Total flux	1180 lm
Luminous efficacy	69 lm/W	Total power	17 W
CCT	3000 K		
CRI	98		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 6.89 in
Width: 3.74 in
Height: 1.93 in

Adjustability

Tiltable

Design

Color of housing: White

Electric

System power: 17 W
Appliance Class: II

Protection

IP: 44