Product data sheet

SLOIN SLIM SL LED5400-827 LDE L3504 PC F
42184663
ZUMTOBEL



DALI-dimmable LED light line with LED converter; with cover to 42m from one piece; LED service life lasts 50000 h before luminous flux is reduced to 85% of the initial value. Chromaticity tolerance (initial MacAdam): 3. Luminaire luminous flux: 5310 lm, Luminaire efficacy: 68 lm/W. Colour rendering Ra > 80, colour temperature 2700 K. Luminaire of aluminium, silver powder coated. Luminaire with completely uniform appearance due to polycarbonate cover. Luminaire consists of housing and continuous optic of polycarbonate. Includes gear tray, wiring, and end-cap set. Luminaire wired with halogen-free leads and covers are due to norm classified as TP(a). Degree of protection: IP20. Dimensions: 3504 x 45 x 64 mm weight: 9 kg

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	78 W	CRI	80
Total flux	5310 lm	LOR	100%
Luminous efficacy	68 lm/W	Total power	78 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 137.95 in
Width: 1.77 in
Height: 2.52 in
Weight: 9 kg

Design

Material impression: Aluminum
Color of housing: Silver gray

Electric

System power: 78 W
Voltage: 220-240 V AC
Controller: DALI
Appliance Class: I

Protection

IP: 20
Designation labels: CE, ENEC