Product data sheet


ODESSA 23 FLOODLIGHTS,PROJECTORS AND COLUMN PROJECTORS
OD-21081-VW-8040
LIGMAN



IP 66 IK 08


- Lamp COB - CCT / CRI 3000K CRI80, 4000K CRI80 - Die-cast aluminium housing - Pre-treated before powder coating ensuring high corrosion resistance - IP67 version is available upon request - Single cable entry, through wiring upon request - Stainless steel fasteners in grade 304 with zinc flake coating (ZFC) - Durable silicone rubber gasket - High-efficiency optical reflector - Clear toughened glass - Integral control gear - Maximum wind load resistance is 160 km/h

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	70 W	CRI	80
Total flux	7914 lm	LOR	100%
Luminous efficacy	113 lm/W	ULOR	50%
		Total power	70 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	70 W	CRI	80
Total flux	7914 lm	LOR	100%
Luminous efficacy	113 lm/W	ULOR	50%
		Total power	70 W

Light output 3 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	70 W	CRI	80
Total flux	7914 lm	LOR	100%
Luminous efficacy	113 lm/W	ULOR	50%
		Total power	70 W

Light output 4 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	70 W	CRI	80
Total flux	7914 lm	LOR	100%
Luminous efficacy	113 lm/W	ULOR	50%
		Total power	70 W

Mounting mode

Standing / Bollard, Pole integrated

Shape and measurements

Height: 236.22 in

Diameter: 7.48 in

Weight: 92.5 kg

Adjustability

Free

Electric

System power: 280 W

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Protection

IP: 66

IK: 08

Surface temperature: 40°C