Product data sheet

PASCALA EVO ROUND
901577.004.76
RZB



IP 20

Series: Pascala Type of Protection: IP 20 Protection Class: II Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Installation and bezel ring: die cast aluminium. Bracket: galvanised sheet steel. Reflector: highly polished aluminium (MIRO-SILVER with 98% total light reflection). Heat sink: extruded aluminium profile. Ceiling mount: spring system. External converter with connecting cable. LED included. Available Colours: silver, metallic Type of Installation: Recessed ceiling mounting Dimensions: D 241, H 2 Lamp: LED Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Luminaire flux LED: 3150lm System power: 31W Beam Angle: 65° Number of fittings B10A: 15 Number of fittings B16A: 24 Number of fittings C10A: 24 Number of fittings C16A: 40 Inrush current: 20,4A Unified Glare Ratio: 18,2 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	31 W	CRI	80
Total flux	3150 lm	LOR	100%
Luminous efficacy	102 lm/W	Total power	31 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.04 in
Diameter: 9.49 in

Adjustability

Fixed

Electric

System power: 31 W

Protection

IP: 20