
# Product data sheet


LESS IS MORE 50
312307.003.1.76
RZB



IP 20 IK 03

Series: LESS IS MORE 50 Linear ceiling and wall luminaire for aesthetically sophisticated lighting. Housing made of extruded aluminium profile, powder-coated. End cap made of aluminium powder-coated. Diffuser made of non-yellowing plastic (PMMA), opal. Suitable for Ceiling mounting. LED unit with integrated converter interchangeable and removable. Suitable for through-wiring. With sensors or as a safety luminaire on request. Colour: deep black, matt (RAL 9005) Length: 1407 mm Width: 57 mm Height: 75 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 34 W Rated luminous flux: 4050 lm Beam angle Down: 106° Luminous efficiency: 119 lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP 20

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 34 W | CRI | 80 |
| Total flux | 4050 lm | LOR | 67% |
| Luminous efficacy | 119 lm/W | ULOR | 14% |
| | | Total power | 34 W |

### Mounting mode

Ceiling mounted

### Shape and measurements

Length: 2.24 in
Width: 55.39 in
Height: 2.95 in

### Adjustability

Fixed

### Design

Color of housing: Black

### Electric

System power: 34 W

### Protection

IP: 20
IK: 03