Product data sheet

LUCAS I (WALL FITTING BEADED) 9.835.3142.16

LEIPZIGER LEUCHTEN









Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp			
Nominal lamp power	50 W		
Lamp flux	2000 lm		
Luminous efficacy	28 lm/W		
CCT	3400 K		
CRI	54		

LOR	83%
ULOR	2%
Total flux	1658 lm
Total power	59 W



I x High pressure mercury vapour lamp				
Nominal lamp power	80 W	LOR	83%	
Lamp flux	4000 lm	ULOR	2%	
Luminous efficacy	37 lm/W	Total flux	3316 lm	
CCT	3400 K	Total power	89 W	
CRI	54			

Mounting mode

Wall mounted

Shape and measurements

Height: 22.44 in Diameter: 22.44 in

Design

Material impression: Matt Color of housing: White Electric

System power: 59-89 W

Ballast: ECG Controller: DALI

Integrated sensors

Integrated sensors: Motion sensor

Protection

IP: 55

Designation labels: CE

Other operating numbers

Ambient temperature range: -4...95°F