


Product data sheet

TENTEC ZONO RECESSED LUMINAIRE, DIFFUSING SCREEN
TL1162214-01-40 + 81010R18
SCHMITZ | WILA



Tentec zono LED 4000 K Recessed Luminaire, Light distribution direct Downlight with lite optic Diffusing Screen Product: TL1162214-01-40 Lite Optic: 81010R18 Lite Optic Diffusing Screen Tempered safety glass For soft dispersion of light in the room Supporting ring white Light Technique Colour rendering index CRI > 80 Colour consistency <3-step MacAdams (SDCM) 50.000 h lifetime (L80/B10) Reflector finish high reflective, white Luminaire housing Robust housing made of die-cast aluminium Passive temperature management Operating and assembly technology LED driver integrated Driver suitable for connection to central battery systems Threaded multi-point fixing, for ceiling thicknesses 1-25mm MS-3 mounting technique for a tool-free change of Liteoptics Lamp Wattage: 12 W Colour Rendering Index: 80 Colour Temperature: 4000 K Luminaire Luminous Flux: 1500 Lm System Efficiency: 115 Lm/W Luminance $\gamma \geq 65^\circ$: --- UGR: 25 Number Luminaires LZ: 0.10 Connector: plug-in terminal, 2 x 1.5 mm2, with loop-in function Reflector Size: R18 Diameter D: 210 mm Cut-out CO: 195 mm Installation Depth RD: 120 mm Total Weight: 1.3 kg Degree of Protection IP44, IP44 in closed ceiling systems CE-Sign Total system: Protection class 2 Data record TL1162214-01-40+81010R18

Light output 1



1 x General service incandescent lamp

Nominal lamp power	13 W	LOR	100%
Lamp flux	1500 lm	Total flux	1499 lm
Luminous efficacy	115 lm/W	Total power	13 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 4.72 in

Diameter: 8.27 in

Adjustability

Fixed

Electric

System power: 13 W

Appliance Class: II

Protection

IP: 44