



Product data sheet

LD43G 1.1W 350MA NB
LD43G-C1-350-NB
LIGHTGRAPHIX



LD43G Ø36mm Recessed Uplight. Constant Current. 1.1W 350mA 12° Narrow spot beam. The new Trimless family is an exciting new addition to the LightGraphix product portfolio, offering lighting designers a modern aesthetic for their projects. They have been made possible by the modularisation of some of our existing fittings. The LD43G is a dual-purpose, recessed, miniature LED uplight and wall light. Featuring a high-quality, seamless glass bezel, the LD43G blends perfectly into its surroundings and can be used internally or externally. As a miniature fitting, it has very minimal body depth and bezel diameter of 36mm. The LD43G produces an excellent throw of light when more output is required despite its size. It can be configured in a wide variety of beam options and angles.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	1.1 W	CRI	93
Total flux	103 lm	LOR	100%
Luminous efficacy	94 lm/W	Total power	1.1 W

Mounting mode

Floor recessed

Shape and measurements

Height: 1.30 in
Diameter: 1.42 in

Adjustability

Fixed

Design

Material impression: Glass
Color of housing: Black

Electric

System power: 1.1 W
Controller: Dimmable 0..10V, Dimmable 1..10V, DMX, DALI
Appliance Class: III

Protection

IP: 68
IK: 06
Designation labels: CE

Other operating numbers

Ambient temperature range: -4...113°F